



| LINK # | MAX. HEX SIZE |      | R (with shroud) |        |
|--------|---------------|------|-----------------|--------|
|        | [in.]         | [mm] | [in.]           | [mm]   |
| 1      | 2-15/16       | 75   | 2.620           | 66.55  |
| 2      | 3-1/8         | 80   | 2.734           | 69.44  |
| 3      | 3-1/2         | 90   | 2.962           | 75.23  |
| 4      | 3-7/8         | 100  | 3.189           | 81.00  |
| 5      | 4-1/4         | 110  | 3.420           | 86.87  |
| 6      | 4-5/8         | 120  | 3.647           | 92.63  |
| 7      | 5             | 130  | 3.872           | 98.35  |
| * 8    | 5-3/8         | 135  | 4.022           | 102.16 |
| * 9    | 5-3/4         | 145  | 4.259           | 108.18 |
| * 10   | 6-1/8         | 155  | 4.456           | 113.18 |

\* - OVERSIZE LINK, NON-STANDARD

| LINK # | H     |        |
|--------|-------|--------|
|        | [in.] | [mm]   |
| 1 ~ 7  | 9.181 | 233.20 |
| 8 ~ 10 | 9.681 | 245.90 |

© COPYRIGHT 2006 UNEX CORP.

"This drawing is the property of the UNEX Corporation and the information thereon is to be treated as confidential. It is not to be used, copied or disclosed to outside parties without our written consent."

TITLE: STEALTH 22

HYTORC