



LINK #	MAX. HEX SIZE		R (with shroud)	
	[in.]	[mm]	[in.]	[mm]
1	3 1/2	90	3.067	77.90
2	3-7/8	100	3.299	83.79
3	4 1/4	110	3.530	89.66
4	4 5/8	120	3.757	95.43
5	5	130	3.984	101.19
6	5 3/8	135	4.144	105.26
7	5 3/4	145	4.363	110.82
8	6 1/8	155	4.581	116.36
9	6 1/2	165	4.800	121.92
*10	6-7/8	175	5.019	127.48
*11	7 1/4	180	5.228	132.79
*12	7 5/8	190	5.456	138.58
*13	8	200	5.680	144.27

\* - OVERSIZE LINK, NON-STANDARD

LINK #	H		L	
	[in.]	[mm]	[in.]	[mm]
1 ~ 9	10.809	274.55	12.708	322.78
10 ~ 11	11.439	290.55	12.708	322.78
12	11.809	299.95	12.708	322.78
13	12.309	312.65	14.997	380.92

© COPYRIGHT 2006 UNEX CORP.

TITLE: STEALTH 36

**HYTORC**

"This drawing is the property of the UNEX Corporation and the information thereon is to be treated as confidential. It is not to be used, copied or disclosed to outside parties without our written consent."